

Bridge Rectifiers





Features

- UL recognition, file #E230084
- Ideal for printed circuit boards
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

General purpose use in AC/DC bridge full wave rectification for monitor, TV, printer, power supply, switching mode power supply, adapter, audio equipment, and home appliances applications.

Mechanical Data

- **Package**: GBP
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

■Maximum Ratings (T_a=25℃ Unless otherwise specified)

PARAMETER		SYMBOL	UNIT	GBP3005A	GBP301A	GBP302A	GBP304A	GBP306A	GBP308A	GBP310A
Device marking code				GBP3005A	GBP301A	GBP302A	GBP304A	GBP306A	GBP308A	GBP310A
Repetitive peak reverse voltage		V_{RRM}	V	50	100	200	400	600	800	1000
Average rectified output current @60Hz sine wave, R-load	With heatsink T_C =140℃	IO	A	3.0						
	Without heatsink T_C =70℃									
Surge(non-repetitive)forward current @60Hz half sine wave, 1 cycle, Tj=25℃		IFSM	A	110						
Current squared time @1ms≤t≤8.3ms Tj=25℃, Rating of per diode		I^2t	A^2s	50						
Storage temperature		Tstg	℃	-55 ~+150						
Junction temperature		Tj	℃	-55 ~+150						

■Electrical Characteristics (T_a=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	GBP3005A	GBP301A	GBP302A	GBP304A	GBP306A	GBP308A	GBP310A
Maximum instantaneous forward voltage drop per diode	VF	V	I_{FM}=1.5A	1.00						
Maximum DC reverse current at rated DC blocking voltage per diode	IRRM	μA	V_{RM}=V_{RRM}	5						

■Thermal Characteristics (T_a=25℃ Unless otherwise specified)

PARAMETER		SYMBOL	UNIT	GBP3005A	GBP301A	GBP302A	GBP304A	GBP306A	GBP308A	GBP310A
Thermal Resistance	Between junction and ambient	$R_{\Theta J-A}$	℃/W	47.0						
	Between junction and lead	$R_{\Theta J-L}$		10.0						

■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
GBP3005A THRU GBP310A	B1	1.4	35	2100	4200	TUBE

■ Characteristics (Typical)

FIG1:Io-Tc Curve




FIG2:Surge Forward Current Capability




FIG3: Forward Voltage






FIG4:Typical Reverse Characteristics



■ Outline Dimensions



GBP		
Dim	Min	Max
A	14.25	14.75
B	10.10	10.60
C	1.80	2.20
D	14.25	14.73
E	1.22	1.42
F	0.76	0.86
G	3.70	3.90
H	3.35	3.65
I	0.80	1.10
J	0.35	0.55