

Bridge Rectifiers





Features

- Ideal for automated placement
- High surge current capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C

Typical Applications

General purpose use in AC/DC bridge full wave rectification for SMPS, lighting ballaster, adapter, battery charger, home appliances, office equipment, and telecommunication applications.

Mechanical Data

- **Package**: YBS3
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, Halogen-free
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

■Maximum Ratings (T_a=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	YBSM60005	YBSM6001	YBSM6002	YBSM6004	YBSM6006	YBSM6008	YBSM6010
Device marking code			YBSM60005	YBSM6001	YBSM6002	YBSM6004	YBSM6006	YBSM6008	YBSM6010
Repetitive peak reverse voltage	V_{RRM}	V	50	100	200	400	600	800	1000
Average rectified output current @60Hz sine wave, R-load, Tc=80℃	I_O	A	6.0						
Surge(non-repetitive)forward current @60HZ sine wave, 1 cycle, T_j=25℃	I_{FSM}	A	150						
Current squared time @1ms≤t≤8.3ms Tj=25℃， Rating of per diode	I^2t	A^2s	93.4						
Storage temperature	T_{stg}	℃	-55 ~+150						
Junction temperature	T_j	℃	-55 ~+150						

■Electrical Characteristics（T_a=25℃ Unless otherwise specified）

PARAMETER	YMBO	UNIT	TEST CONDITIONS	YBSM60005	YBSM6001	YBSM6002	YBSM6004	YBSM6006	YBSM6008	YBSM6010
Maximum instantaneous forward voltage drop per diode	V_F	V	I_{FM}=3.0A	1.0						
Maximum DC reverse current at rated DC blocking voltage per diode @ VRM=VRRM	I_{RRM}	μA	Tj=25℃	5						

■Thermal Characteristics （T_a=25℃ Unless otherwise specified）

PARAMETER		SYMBOL	UNIT	YBSM60005	YBSM6001	YBSM6002	YBSM6004	YBSM6006	YBSM6008	YBSM6010
Thermal Resistance	Between Junction and Ambient without heatsink	RθJ-A	℃/W	55(1)						
	Between Junction and Lead without heatsink	RθJ-L		10(1)						
	Between Junction and Case without heatsink	RθJ-C		5(1)						

Note:(1)Thermal resistance mounted on P.C.B with 30mm*15mm.*1.6mm

■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
YBSM60005 THRU YBSM6010	F1	Approximate 0.36	1800	3600	25200	13'' Reel

■ Characteristics(Typical)

FIG1:Io-Tc Curve




FIG2:Surge Forward Current Capability




FIG3: Forward Voltage






FIG4:Typical Reverse Characteristics




■ Outline Dimensions



YBS3		
Dim	Min	Max
A	10.00	10.40
B	9.70	10.10
C	6.80	7.20
D	1.3	1.5
E	1.4	1.8
F	0.5	1.1
G	0	0.15
H	4.9	5.1

■ Suggested pad layout



YBS3	
Dim	**Min**
P1	9.25
P2	5.00
Q1	1.00
Q2	1.5