SAMYANG ELECTRONICS

FR151G --- FR157G

GLASS PASSIVATED RECTIFIERS

VOLTAGE RANGE: 50 --- 1000 V
CURRENT: 1.5 A


FEATURES

- ◇ Low cost
- ◇ Glass passivated junction
- ◇ Low leakage
- ◇ Low forward voltage drop
- ◇ High current capability
- ◇ Easily cleaned with Alcohol,Isopropanol and similar solvents
- ◇ The plastic material carries U/L recognition 94V-0

MECHANICAL DATA

- ◇ Case:JEDEC DO-15,molded plastic
- ◇ Terminals: Axial lead ,solderable per MIL- STD-202,Method 208
- ◇ Polarity: Color band denotes cathode
- ◇ Weight: 0.014 ounces,0.39 grams
- ◇ Mounting position: Any

DO - 15



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25℃ ambient temperature unless otherwise specified.

Single phase,half wave,60 Hz,resistive or inductive load. For capacitive load,derate by 20%.

		FR151G	FR152G	FR153G	FR154G	FR155G	FR156G	FR157G	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum average forward rectified current 9.5mm lead length, @T_A=75℃	$I_{F(AV)}$	1.5							A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load @T_J=125℃	I_{FSM}	60.0							A
Maximum instantaneous forward voltage at 1.5A	V_F	1.3							V
Maximum reverse current @T_A=25℃ at rated DC blocking voltage @T_A=100℃	I_R	5.0 100.0							μA
Maximum reverse recovery time (Note1)	t_{rr}	150				250	500		ns
Typical junction capacitance (Note2)	C_J	18.0							pF
Typical thermal resistance (Note3)	$R_{\theta JA}$	45.0							℃
Operating junction temperature range	T_J	- 55 ---- + 175							℃
Storage temperature range	T_{STG}	- 55 ---- +175							℃


NOTE: 1. Measured with I_F=0.5A, I_R=1A, I_{rr}=0.25A.


2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

3. Thermal resistance junction to ambient

www.diode.co.kr

FIG.1 -- TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC





NOTES:1.RISE TIME = 7ns MAX.INPUT IMPEDANCE =1MΩ. 22pF.
2.RISE TIME =10ns MAX.SOURCE IMPEDANCE=50 Ω.

SET TIME BASE FOR 50/100 ns/cm

FIG.2 --FORWARD DERATING CURVE




FIG.3 -- TYPICAL FORWARD CHARACTERISTICS




FIG.4 --REPE FORWARD SURGE CURRENT




FIG.5-- TYPICAL JUNCTION CAPACITANCE

