SAMYANG ELECTRONICS

SS22A --- SS220A

SCHOTTKY BARRIER RECTIFIER

VOLTAGE RANGE: 20 --- 200 V
CURRENT: 2.0A


FEATURES

- ◇Metal-semiconductor junction with guard ring
- ◇Epitaxial construction
- ◇Low forward voltage drop,low switching losses
- ◇High surge capability
- ◇For use in low voltage,high frequency inverters free wheeling,and polarity protection applications
- ◇The plastic material carries U/L recognition 94V-0

MECHANICAL DATA

- ◇Case:JEDEC SMA(DO-214AC),molded plastic
- ◇Terminals: Axial lead ,solderable per MIL- STD-750,Method 2026
- ◇Polarity: Color band denotes cathode end
- ◇Weight: 0.002 ounces, 0.064 grams
- ◇Mounting position: Any

SMA(DO-214AC)



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25℃ ambient temperature unless otherwise specified.

Single phase,half wave,60 Hz,resistive or inductive load. For capacitive load,derate by 20%.

		V_{RRM}	SS 22A	SS 23A	SS 24A	SS 25A	SS 26A	SS 28A	SS 210A	SS 215A	SS 220A	Volts
Maximum repetitive peak reverse voltage		V_{RRM}	20	30	40	50	60	80	100	150	200	Volts
Maximum RMS voltage		V_{RMS}	14	21	28	35	42	57	71	105	140	Volts
Maximum DC blocking voltage		V_{DC}	20	30	40	50	60	80	100	150	200	Volts
Maximum average forward rectified current (See Fig. 1)		$I_{(AV)}$	2.0									Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)		I_{FSM}	50.0									Amps
Maximum instantaneous forward voltage at 2.0 A(note 1)		V_F	0.55			0.75		0.85		0.90	0.95	Volts
Maximum instantaneous reverse current at rated DC blocking voltage(Note 1)	T_A=25℃	I_R	0. 2									mA
	T_A=100℃		10.0									
Typical thermal resistance (Note 2)		R_{JA} R_{JL}	88.0 28.0									℃/W
Operating junction temperature range		T_J	-65 to+150									℃
Storage temperature range		T_{STG}	-65 to+150									℃

NOTE: 1. Pulse test:300us pulse width,1% duty cycle.
2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.
3.Thermal resistance junction to ambient

www.diode.co.kr

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE

