

Surface Mount Super Fast Recovery Rectifier





Features

- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- High forward surge capability
- Super Fast reverse recovery time
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C

Typical Applications

For use in high frequency rectification of power supplies, inverters, converters, and freewheeling diodes for consumer and telecommunication.

Mechanical Data

- **Package**: DO-214AA (SMB)
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

■Maximum Ratings (Ta=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	ER2A	ER2B	ER2C	ER2D	ER2F	ER2G	ER2H	ER2J	ER2K
Device marking code			ER2A	ER2B	ER2C	ER2D	ER2F	ER2G	ER2H	ER2J	ER2K
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	50	100	150	200	300	400	500	600	800
Maximum RMS Voltage	V_{RMS}	V	35	70	105	140	210	280	350	420	560
Maximum DC blocking Voltage	V_{DC}	V	50	100	150	200	300	400	500	600	800
Average rectified output current @60Hz sine wave, resistance load, TL (Fig.1)	I_O	A	2.0								
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25℃	I_{FSM}	A	50								
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25℃			100								
Current squared time @1ms≤t≤8.3ms Tj=25℃	I^2t	A^2s	10.375								
Storage temperature	T_{stg}	℃	-55 ~ +150								
Junction temperature	T_j	℃	-55 ~ +150								

■Electrical Characteristics (Ta=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	ER2A	ER2B	ER2C	ER2D	ER2F	ER2G	ER2H	ER2J	ER2K
Maximum instantaneous forward voltage	V_F	V	I_{FM}=2.0A	0.95				1.3		1.7		1.85
Maximum reverse recovery time	t_{rr}	ns	I_F=0.5A,I_R=1.0A, Irr=0.25A	35								
Maximum DC reverse current at rated DC blocking voltage	I_R	μA	Tj =25℃	5.0								
			Tj =100℃	500								
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	31				17		12		12

■Thermal Characteristics （T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	ER2A	ER2B	ER2C	ER2D	ER2F	ER2G	ER2H	ER2J	ER2K
Typical Thermal Resistance	$R_{\theta J-A}$(1)	℃/W	60								
	$R_{\theta J-L}$(1)		22								
	$R_{\theta J-C}$(1)		16								

Note:
(1) Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.3" x 0.3" (8.0 mm x 8.0 mm) copper pad areas

■ Characteristics (Typical)

FIG1：Io-TL Curve




FIG2：Surge Forward Current Capability




FIG3: Typical Forward Voltage




FIG4:Typical Reverse Characteristics






FIG.5: Diagram of circuit and Testing wave form of reverse recovery time



■Ordering Information (Example)


PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
ER2A-ER2K	F1	Approximate 0.096	3000	/	48000	13” reel
ER2A-ER2K	F2	Approximate 0.096	750	6000	24000	7” reel
ER2A-ER2K	F3	Approximate 0.096	500	4000	16000	7” reel

■ Outline Dimensions



DO-214AA(SMB)		
Dim	Min	Max
A	1.85	2.15
B	3.30	3.94
C	4.05	4.75
D	1.99	2.61
E	5.21	5.59
F	0.90	1.41
G	0.05	0.20
H	0.15	0.31

■ **Suggested pad layout**



DO-214AA(SMB)	
Dim	Millimeters
P1	6.8
P2	4.3
P3	1.8
Q1	2.5
Q2	2.3